

Finiré Prime

Premium LED Recessed Lighting by Ivalo



Lutron quick-ship fixture solution

- Guaranteed Lutron control compatibility
- Standard Lutron 1% dimming driver with Soft-on, Fade-to-Black options
- 90+ CRI, 1000 Delivered Lumens
- Shallow ceiling options
- EcoSystem option digitally allows individual fixture control



Features and benefits

The Ivalo Difference



Guaranteed compatibility with Lutron controls



Standard Lutron driver with EcoSystem Soft-on, Fade-to-Black option



LED Control Center of Excellence and 24/7 technical support

Why Choose Finiré Prime?



Low profile 3.5" shallow Non-IC housing



5-year limited Lutron warranty




Quick-ship stocked solutions



High LED color quality R9=50+



Consistent color from fixture-to-fixture



Standard 1,000 delivered lumens

Finiré Prime Specifications

LED Performance

Finiré Model	Standard
CRI	90+, R9=50+
Lumens (Delivered)	1000
Wattage	14
Efficacy (Lumens/Watt)	71

Fixture Dimensions

Trim	5.0" W
Aperture	3.0" W
Non-IC Housing	10.5" L x 7.8" W x 3.5" H
IC Housing	18.9" L x 9.5" W x 6.0" H
Max Ceiling Thickness	up to 5/8"

Independent measurement of typical 3000K downlight fixture models by Lutron Electronics Co., Inc. for reference only. See the Finiré Prime specification sheets for LM79 photometric data by fixture type and trim options.

Fixture Types & Options

IC and shallow non-IC housing options

Securely clips into ceiling without additional hardware

30° and 65° beam spreads

Tilts up to 25°

Round or square trim in Matte White

2700K and 3000K 90+ CRI LED options, 14W, 1000 lumen output



Compatible Controls

For a list of compatible controls, visit lutron.com/finire or contact the LED Control Center of Excellence at leds@lutron.com/1.877.DIM.LED8.

How to specify Finiré Prime LED Recessed Lighting

Specifying Finiré Prime is Easier Than

1

2

3

Trim (includes LED module)

- 1 Do you like round or square?
- 2 How warm would you like your light?
- 3 Which beam spread is needed?

FPAT R 27X 30 MW

Family

FPAT = Finiré Prime, Adjustable, Trimmed

1

Shape

R = Round
S = Square

2

LED Type

27X = 2700K, 14W, 1000lm, 90+ CRI
30X = 3000K, 14W, 1000lm, 90+ CRI

3

Beam Spread

30 = 30°
65 = 65°

Finish

MW = Matte White trim

Housing

- 1 Does your ceiling use insulation?
- 2 Which control type is needed?

FPH NX F1

Family

FPH = Finiré Prime Housing

1

Housing Type

NX = Non-insulation Contact (Non-IC)
IX = Insulation Contact (IC)

2

Control Type

F1 = 2-wire, 120V
EU = EcoSystem, 120-277 V



lutron.com/ivalo

Lutron Electronics Co., Inc.
7200 Suter Road
Coopersburg, PA 18036-1299

Customer Service and 24/7 Technical Support:
610.282.7472 or fixtures@lutron.com

© 5/2017 Lutron Electronics Co., Inc.
Printed in the U.S.A.
P/N 367-2714 REV B



Coming Soon!

Lutron, Finiré, and EcoSystem are trademarks of Lutron Electronics Co., Inc, registered in the U.S. and other countries.

Soft-on, Fade-to-Black is a trademark of Lutron Electronics Co., Inc.